SAFETY DATA SHEET



1. Identification

Product identifier Cleaning Carnuba Wax

Other means of identification

Product code MRS-CleanerWax

Recommended use Polish

Recommended restrictions No other uses are advised. **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company nameMedallion Refinish SystemAddress5751 N. Webster StreetDavton, OH 45414

United States

Telephone TECH SUPPORT

SALES 937-890-6547 PHONE 800-257-6547

Websitewww.medallionrefinish.comE-mailinfo@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F 800-257-6547

7:45am-4:30pm

EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

937-890-6547

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSerious eye damage/eye irritationCategory 2AGerm cell mutagenicityCategory 1BCarcinogenicityCategory 1BAspiration hazardCategory 1Environmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes serious eye

irritation. May cause genetic defects. May cause cancer. Harmful to aquatic life with long lasting

Category 3

effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: Cleaning Carnuba Wax sps us

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Response

Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists:

Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

21.01% of the mixture consists of component(s) of unknown acute oral toxicity. 21.01% of the mixture consists of component(s) of unknown acute dermal toxicity. 6.96% of the mixture consists of component(s) of unknown acute inhalation toxicity. 6.96% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 6.96% of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha, Petroleum, Heavy Alkylate		64741-65-7	10 - < 20
White Mineral Oil		8042-47-5	1 - < 3
Alcohols, C8-22, Ethoxylated		69013-19-0	< 1
Methanol		67-56-1	< 0.1
Sodium Hydroxide		1310-73-2	< 0.1
Titanium Dioxide		13463-67-7	< 0.1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth, Do not induce vomiting, If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: Cleaning Carnuba Wax

2/9 MRS-CleanerWax Version #: 03 Revision date: 02-08-2017 Issue date: 10-07-2016

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Type	Value	Form
Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)	PEL	400 mg/m3	
,		100 ppm	
White Mineral Oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)	TWA	400 mg/m3	
,		100 ppm	
White Mineral Oil (CAS 3042-47-5)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
ogical limit values	No biological exposure limits noted f	or the ingredient(s).	

Biological limit values

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Not available.

Material name: Cleaning Carnuba Wax

Odor Not available. **Odor threshold** Not available. Ηq Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

356 °F (180 °C) estimated

89.6 °F (32.0 °C) Pensky-Martens Closed Cup Flash point

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.7 % estimated

Flammability limit - upper

(%)

5.4 % estimated

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperature Not available. Not available. **Viscosity**

Other information

0.67 g/cm3 estimated **Density**

Not explosive. **Explosive properties**

Flammability class Flammable IC estimated

Not oxidizing. **Oxidizing properties** 15.06 % estimated Percent volatile 0.67 estimated Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Hazardous polymerization does not occur. Possibility of hazardous

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eve contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Material name: Cleaning Carnuba Wax

SDS US

MRS-CleanerWax Version #: 03 Revision date: 02-08-2017 Issue date: 10-07-2016

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

White Mineral Oil (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
LCOLOXICILY	riammar to aquatio me with long lacting encote.

Components		Species	Test Results
Naphtha, Petroleum, I	Heavy Alkylate (CA	S 64741-65-7)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

8.8 mg/l, 96 hours

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: Cleaning Carnuba Wax

sps us 6 / 9

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number UN1993

UN proper shipping name Flammable liquids, n.o.s. (Naphtha, Petroleum, Heavy Alkylate)

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T4, TP1, TP29 Special provisions

Packaging exceptions 150 Packaging non bulk 203 242 Packaging bulk

IATA

UN number UN1993

UN proper shipping name Flammable liquid, n.o.s. (Naphtha, Petroleum, Heavy Alkylate)

Transport hazard class(es)

3 **Class** Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Naphtha, Petroleum, Heavy Alkylate)

Allowed with restrictions.

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No. F-E, S-E

EmS

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established. Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Material name: Cleaning Carnuba Wax

MRS-CleanerWax Version #: 03 Revision date: 02-08-2017 Issue date: 10-07-2016



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Naphtha, Petroleum, Heavy Alkylate (CAS 64741-65-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region Inventory name On inventory (yes/no)*

Europe European Inventory of Existing Commercial Chemical

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No

Japan Inventory of Existing and New Chemical Substances (ENCS) No

Korea Existing Chemicals List (ECL)

No
New Zealand

New Zealand Inventory

No

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 10-07-2016

 Revision date
 02-08-2017

Version # 03

Disclaimer Medallion Refinish System cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the

product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision information Product and Company Identification: Product and Company Identification

Hazard(s) identification: Hazard statement

Hazard(s) identification: Hazard(s) not otherwise classified (HNOC)

Composition / Information on Ingredients: Ingredients Fire-fighting measures: Suitable extinguishing media

Fire-fighting measures: Specific hazards arising from the chemical

Fire-fighting measures: General fire hazards

Accidental release measures: Personal precautions, protective equipment and emergency

procedures

Accidental release measures: Environmental precautions Handling and storage: Precautions for safe handling

Handling and storage: Conditions for safe storage, including any incompatibilities

Exposure controls/personal protection: Appropriate engineering controls

Physical & Chemical Properties: Multiple Properties

Material name: Cleaning Carnuba Wax

MRS-CleanerWax Version #: 03 Revision date: 02-08-2017 Issue date: 10-07-2016