



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Toll-Free 937-890-6547
Phone 800-257-6547
Fax 937-890-6320

RS-135

TECHNICAL DATA

Rubber Glue

DESCRIPTION:

RS-135 is a fast drying contact cement in a flammable solvent system. It offers rapid strength build-up, high ultimate strength with greater than normal open time, and a high softening point. The adhesive has excellent specific adhesion to metal and finds use in bonding all types of rubber, vinyl and decorative plastic laminates for use in the automotive soft trim applications. This adhesive combines high heat resistance with oil resistance making it ideal for bonding flexible stock containing non-permanent plasticizers.



APPLICATION INSTRUCTIONS:

1. Remove all wax, grease and other contaminants
2. Apply adhesive to one surface
3. Join surfaces to distribute adhesive then pull back apart
4. Wait 30 seconds and join surfaces for final bond

TECHNICAL DATA:

Color	Clear Translucent
Base	Resin Modified Neoprene Rubber
Solvent	Ketone Hydrocarbon Blend
Viscosity	Brookfield 2/20 800 + 50 Cps.
Solids	23% + 1%
Specific Gravity	7.0 + 0.1 lbs./gal.
Flash Point	-12°F

TM

Medallion
Refinish System