

1. Identification

Product identifier	Basemate Reducer Fast		
Other means of identification			
Product code	RS-1760		
Recommended use	Reducer		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Medallion Refinish System		
Address	5751 N. Webster Street Dayton, OH 45414 United States		
Telephone	TECH SUPPORT	937-890-6547	
	SALES	937-890-6547	
	PHONE	800-257-6547	
Website	www.medallionrefinish.com		
E-mail	info@rubber-seal.net		
Contact person	Elizabeth Wells		
Emergency phone number	MAIN OFFICE: M-F	800-257-6547	
	7:45am-4:30pm		
	EMERGENCY 24 Hrs.	800-424-9300 ChemTrec	

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	68.54% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethyl Acetate 99%		141-78-6	50 - < 70
2,6-Dimethyl-4-heptanone		108-83-8	10 - < 20
N-Butyl Acetate		123-86-4	10 - < 20
Methyl Ethyl Ketone		78-93-3	5 - < 10
Glycol Ether PM Acetate		108-65-6	0 < 5
Methyl Isobutyl Ketone		108-10-1	0 - < 5
Methyl n-Amyl Ketone		110-43-0	0 < 5
Phosphoric Acid Regulatory		7664-38-2	0 < 5
Silica, amorphous, precipitated and gel		112926-00-8	0 < 5
Silicon dioxide		112945-52-5	0 < 5
Other components below reportable levels			< 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
-------------------------------------	---

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".
--------------------------------------	---

**Conditions for safe storage,
including any incompatibilities**

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	PEL	290 mg/m3
Ethyl Acetate 99% (CAS 141-78-6)	PEL	50 ppm 1400 mg/m3
Methyl Ethyl Ketone (CAS 78-93-3)	PEL	400 ppm 590 mg/m3
Methyl Isobutyl Ketone (CAS 108-10-1)	PEL	200 ppm 410 mg/m3
Methyl n-Amyl Ketone (CAS 110-43-0)	PEL	100 ppm 465 mg/m3
N-Butyl Acetate (CAS 123-86-4)	PEL	100 ppm 710 mg/m3
Phosphoric Acid Regulatory (CAS 7664-38-2)	PEL	150 ppm 1 mg/m3

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Silica, amorphous, precipitated and gel (CAS 112926-00-8)	TWA	0.8 mg/m3
Silicon dioxide (CAS 112945-52-5)	TWA	20 mppcf 0.8 mg/m3
		20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	TWA	25 ppm
Ethyl Acetate 99% (CAS 141-78-6)	TWA	400 ppm
Methyl Ethyl Ketone (CAS 78-93-3)	STEL	300 ppm
Methyl Isobutyl Ketone (CAS 108-10-1)	TWA	200 ppm
	STEL	75 ppm
Methyl n-Amyl Ketone (CAS 110-43-0)	TWA	20 ppm
N-Butyl Acetate (CAS 123-86-4)	TWA	50 ppm
	STEL	200 ppm
Phosphoric Acid Regulatory (CAS 7664-38-2)	TWA	150 ppm
	STEL	3 mg/m3
	TWA	1 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2,6-Dimethyl-4-heptanone (CAS 108-83-8)	TWA	150 mg/m3
Ethyl Acetate 99% (CAS 141-78-6)	TWA	25 ppm 1400 mg/m3
Methyl Ethyl Ketone (CAS 78-93-3)	STEL	400 ppm 885 mg/m3
Methyl Isobutyl Ketone (CAS 108-10-1)	TWA	300 ppm 590 mg/m3
	STEL	200 ppm 300 mg/m3
Methyl n-Amyl Ketone (CAS 110-43-0)	TWA	75 ppm 205 mg/m3
		50 ppm 465 mg/m3
N-Butyl Acetate (CAS 123-86-4)	STEL	100 ppm 950 mg/m3
	TWA	200 ppm 710 mg/m3
Phosphoric Acid Regulatory (CAS 7664-38-2)	STEL	150 ppm 3 mg/m3
	TWA	1 mg/m3
Silica, amorphous, precipitated and gel (CAS 112926-00-8)	TWA	6 mg/m3
Silicon dioxide (CAS 112945-52-5)	TWA	6 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Methyl Ethyl Ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Methyl Isobutyl Ketone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines
US - California OELs: Skin designation

Glycol Ether PM Acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment
Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection
Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Colorless
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-123.95 °F (-86.64 °C) estimated
Initial boiling point and boiling range	170.6 °F (77 °C) estimated
Flash point	15.8 °F (-9.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	0.8 % estimated
Flammability limit - upper (%)	10 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	90.7 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	745 °F (396.11 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

Density	0.87 g/cm3 estimated
Flammability class	Flammable IB estimated
Percent volatile	99.19 w/w % By Weight 99.45 v/v % By Volume
Specific gravity	0.87 estimated
VOC (Weight %)	7.25 lb/gal (Actual VOC - With Water Less Exempts) 7.25 lb/gal (Regulatory VOC - Less Water Less Exempts) 868.92 g/L (Regulatory VOC - Less Water Less Exempts) 868.92 g/L (Actual VOC - With Water With Exempts)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Ammonia. Amines. Isocyanates. Caustics.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Toxic if inhaled. Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
2,6-Dimethyl-4-heptanone (CAS 108-83-8)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	16200 mg/kg
	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l, 4 Hours
Oral		
LD50	Mouse	1416 mg/kg
	Rat	5285 mg/kg
Ethyl Acetate 99% (CAS 141-78-6)		
<u>Acute</u>		
Inhalation		
LC50	Rat	16000 ppm, 6 Hours
LD50	Mouse	1500 ppm, 4 Hours
	Rabbit	2500 ppm, 4 Hours
	Rat	4000 ppm, 4 Hours
Oral		
LD50	Mouse	0.44 g/kg
	Rabbit	4.9 g/kg
	Rat	11.3 ml/kg
		5.6 g/kg
Methyl Ethyl Ketone (CAS 78-93-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 8000 mg/kg
Inhalation		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours

Components	Species	Test Results
Oral		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
Methyl Isobutyl Ketone (CAS 108-10-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Oral		
LD50	Rat	2080 mg/kg
Methyl n-Amyl Ketone (CAS 110-43-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12600 mg/kg
Oral		
LD50	Mouse	730 mg/kg
	Rat	1.67 g/kg
N-Butyl Acetate (CAS 123-86-4)		
<u>Acute</u>		
Inhalation		
LC50	Wistar rat	160 mg/l, 4 Hours
Oral		
LD50	Rat	14000 mg/kg
Phosphoric Acid Regulatory (CAS 7664-38-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	2740 mg/kg
Oral		
LD50	Rat	1530 mg/kg
Silica, amorphous, precipitated and gel (CAS 112926-00-8)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Silicon dioxide (CAS 112945-52-5)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Isobutyl Ketone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Silica, amorphous, precipitated and gel (CAS 112926-00-8)	3 Not classifiable as to carcinogenicity to humans.
Silicon dioxide (CAS 112945-52-5)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results
Ethyl Acetate 99% (CAS 141-78-6)		
Aquatic		
Fish	LC50	Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours
Methyl Ethyl Ketone (CAS 78-93-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus) > 400 mg/l, 96 hours
Methyl Isobutyl Ketone (CAS 108-10-1)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours
Methyl n-Amyl Ketone (CAS 110-43-0)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 126 - 137 mg/l, 96 hours
N-Butyl Acetate (CAS 123-86-4)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
--------------------------------------	--

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethyl Acetate 99%	0.73
Methyl Ethyl Ketone	0.29
Methyl Isobutyl Ketone	1.31
Methyl n-Amyl Ketone	1.98
N-Butyl Acetate	1.78

Mobility in soil	No data available.
-------------------------	--------------------

Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
------------------------------	---

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT	
UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
IATA	
UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl Acetate 99% (CAS 141-78-6)	Listed.
Methyl Ethyl Ketone (CAS 78-93-3)	Listed.
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed.
N-Butyl Acetate (CAS 123-86-4)	Listed.
Phosphoric Acid Regulatory (CAS 7664-38-2)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methyl Isobutyl Ketone	108-10-1	0 - < 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methyl Isobutyl Ketone (CAS 108-10-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Methyl Ethyl Ketone (CAS 78-93-3)	6714
Methyl Isobutyl Ketone (CAS 108-10-1)	6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Methyl Ethyl Ketone (CAS 78-93-3)	35 %WV
Methyl Isobutyl Ketone (CAS 108-10-1)	35 %WV

DEA Exempt Chemical Mixtures Code Number

Methyl Ethyl Ketone (CAS 78-93-3)	6714
Methyl Isobutyl Ketone (CAS 108-10-1)	6715

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
Phosphoric Acid Regulatory (CAS 7664-38-2)

US. Massachusetts RTK - Substance List

2,6-Dimethyl-4-heptanone (CAS 108-83-8)
Ethyl Acetate 99% (CAS 141-78-6)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
Methyl n-Amyl Ketone (CAS 110-43-0)
N-Butyl Acetate (CAS 123-86-4)
Phosphoric Acid Regulatory (CAS 7664-38-2)
Silica, amorphous, precipitated and gel (CAS 112926-00-8)
Silicon dioxide (CAS 112945-52-5)

US. New Jersey Worker and Community Right-to-Know Act

2,6-Dimethyl-4-heptanone (CAS 108-83-8)
Ethyl Acetate 99% (CAS 141-78-6)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
Methyl n-Amyl Ketone (CAS 110-43-0)
N-Butyl Acetate (CAS 123-86-4)
Phosphoric Acid Regulatory (CAS 7664-38-2)
Silica, amorphous, precipitated and gel (CAS 112926-00-8)

US. Pennsylvania Worker and Community Right-to-Know Law

2,6-Dimethyl-4-heptanone (CAS 108-83-8)
Ethyl Acetate 99% (CAS 141-78-6)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
Methyl n-Amyl Ketone (CAS 110-43-0)
N-Butyl Acetate (CAS 123-86-4)
Phosphoric Acid Regulatory (CAS 7664-38-2)
Silicon dioxide (CAS 112945-52-5)

US. Rhode Island RTK

Ethyl Acetate 99% (CAS 141-78-6)
Methyl Ethyl Ketone (CAS 78-93-3)
Methyl Isobutyl Ketone (CAS 108-10-1)
N-Butyl Acetate (CAS 123-86-4)
Phosphoric Acid Regulatory (CAS 7664-38-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methyl Isobutyl Ketone (CAS 108-10-1)	Listed: November 4, 2011
---------------------------------------	--------------------------

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methyl Isobutyl Ketone (CAS 108-10-1)	Listed: March 28, 2014
---------------------------------------	------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-12-2015

Version # 01

Disclaimer Medallion Refinish System cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.