



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Toll-Free 937-890-6547
Phone 800-257-6547
Fax 937-890-6320

RS-293

TECHNICAL DATA

Joint Seal

DESCRIPTION:

RS-293 is a medium cure time flexible seam sealer for all types of auto body sealing. Joint seal has a longer open time so it can be tooled for several minutes after applied. Joint seal tools very smooth, even without solvent. Can be tooled with solvent for extra slick appearance. Can be painted 30-60 minutes after applied. Skin time is approximately 10 minutes. Sets to a firm abrasion resistant seal. No cracks or peeling.



APPLICATION:

1. Be sure material and surface are at room temperature (72°F)
2. Apply only to clean dry surface.
3. Smooth out with tool or finger and featheredge with RS-600 AcryLac or Enamel Reducer.
4. Any type of paint can be applied after 30 minutes.
5. Clean any excess with AcryLac before RS-293 sets up.

RUBBER-SEAL®

Medallion™
Refinish System



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Toll-Free 937-890-6547
Phone 800-257-6547
Fax 937-890-6320



FEATURES AND BENEFITS:

Features:

- Rubber Base
- Medium setting time
- Smooth easy-to-work formula
- Heavy non-sag formula
- Non shrink formula
- Compatible with all primers and paint finishes
- Tough and mar-resistant when cured

Benefits:

- Excellent flexibility
- Skin time approximately 10 minutes. Paintable in one hour.
- Tools easily and smoothly to a perfect factory match.
- Stands up on vertical surfaces
- Won't crack even in large seams
- Can be applied over unprimed or primed surfaces. Accepts all paints.
- Excellent for exposed applications (i.e. door skins, trunk seams, etc.)

