

1. Identification

Product identifier Self Etching Primer

Other means of identification

Product code RS-786 (all sizes)

Recommended use Primer

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Medallion Refinish System

Address 5751 N. Webster Street
Dayton, OH 45414
United States

Telephone TECH SUPPORT 937-890-6547
SALES 937-890-6547
PHONE 800-257-6547

Website www.medallionrefinish.com

E-mail info@rubber-seal.net

Contact person Elizabeth Wells

Emergency phone number MAIN OFFICE: M-F 800-257-6547
7:45am-4:30pm
EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Harmful if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe the mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Rinse mouth. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

23.48% of the mixture consists of component(s) of unknown acute oral toxicity. 48.25% of the mixture consists of component(s) of unknown acute inhalation toxicity. 50.92% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 50.92% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	20 - < 40
Isobutyl Alcohol		78-83-1	5 - < 20
Isopropanol		67-63-0	5 - < 20
Glycol Ether PM Acetate		108-65-6	5 - < 10
Toluene		108-88-3	5 - < 10
Aluminum Hydroxide Regulatory		21645-51-2	0 < 5
Barium Sulfate		7727-43-7	0 - < 5
Calcium Carbonate		1317-65-3	0 - < 5
Carbon Black		1333-86-4	0 < 5
Crystalline Quartz Regulatory		14808-60-7	0 < 5
Ethylbenzene		100-41-4	0 < 5
Formaldehyde Regulatory		50-00-0	0 < 5
Methanol		67-56-1	0 - < 5
Methyl Isobutyl Ketone		108-10-1	0 < 5
Petroleum Distillates, Hydrotreated Light Regulatory		64742-47-8	0 < 5
Phenol		108-95-2	0 < 5
Silica		7631-86-9	0 < 5
Silicon dioxide		112945-52-5	0 < 5
Solvent Naphtha, petroleum, light aromatic		64742-95-6	0 < 5
Titanium Dioxide		13463-67-7	0 - < 5
Xylene		1330-20-7	0 - < 5
Other components below reportable levels			5 - < 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Formaldehyde Regulatory (CAS 50-00-0)	STEL	2 ppm
	TWA	0.75 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Isobutyl Alcohol (CAS 78-83-1)	PEL	300 mg/m3	
		100 ppm	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	
Methyl Isobutyl Ketone (CAS 108-10-1)	PEL	410 mg/m3	
		100 ppm	
Phenol (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Quartz Regulatory (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Silicon dioxide (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum Hydroxide Regulatory (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline Quartz Regulatory (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Formaldehyde Regulatory (CAS 50-00-0)	Ceiling	0.3 ppm	
Isobutyl Alcohol (CAS 78-83-1)	TWA	50 ppm	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
Methyl Isobutyl Ketone (CAS 108-10-1)	STEL	75 ppm	
	TWA	20 ppm	
Phenol (CAS 108-95-2)	TWA	5 ppm	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Crystalline Quartz Regulatory (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	
Formaldehyde Regulatory (CAS 50-00-0)	Ceiling	0.1 ppm	
	TWA	0.016 ppm	
Isobutyl Alcohol (CAS 78-83-1)	TWA	150 mg/m3	
		50 ppm	
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Methanol (CAS 67-56-1)	STEL	325 mg/m3	
		250 ppm	
	TWA	260 mg/m3	
		200 ppm	
Methyl Isobutyl Ketone (CAS 108-10-1)	STEL	300 mg/m3	
		75 ppm	
	TWA	205 mg/m3	
		50 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)	TWA	100 mg/m3	
Phenol (CAS 108-95-2)	Ceiling	60 mg/m3 15.6 ppm	
	TWA	19 mg/m3 5 ppm	
Silica (CAS 7631-86-9)	TWA	6 mg/m3	
Silicon dioxide (CAS 112945-52-5)	TWA	6 mg/m3	
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm	
	TWA	375 mg/m3 100 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Methyl Isobutyl Ketone (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines
US - California OELs: Skin designation

Glycol Ether PM Acetate (CAS 108-65-6)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)	Skin designation applies.
Phenol (CAS 108-95-2)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)	Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Phenol (CAS 108-95-2)	Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

Phenol (CAS 108-95-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Liquid.

Color

Gray

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-173.38 °F (-114.1 °C) estimated

Initial boiling point and boiling range

173.3 °F (78.5 °C) estimated

Flash point

40.0 °F (4.4 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

1.2 % estimated

Flammability limit - upper (%)

12 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

51.2 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)**Solubility (water)**

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

685 °F (362.78 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density	1.06 g/cm3 estimated
Flammability class	Flammable IB estimated
Percent volatile	78.39 w/w % By Weight 87.72 v/v % By Volume
Specific gravity	1.06 estimated
VOC (Weight %)	6.04 lb/gal (Actual VOC - With Water With Exempts) 6.04 lb/gal (Regulatory VOC - Less Water Less Exempts) 723.94 g/L (Actual VOC - With Water With Exempts) 723.96 g/L (Regulatory VOC - Less Water Less Exempts)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Halogens. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.
Ingestion	Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	Harmful if inhaled. Harmful if swallowed. Narcotic effects.
----------------	---

Components	Species	Test Results
Aluminum Hydroxide Regulatory (CAS 21645-51-2)		
<u>Acute</u>		
<u>Oral</u>		
LD50	Rat	> 5000 mg/kg
Carbon Black (CAS 1333-86-4)		
<u>Acute</u>		
<u>Oral</u>		
LD50	Rat	> 8000 mg/kg
Ethanol (CAS 64-17-5)		
<u>Acute</u>		
<u>Inhalation</u>		
LC50	Mouse	39 mg/l, 4 Hours
	Rat	20000 ppm, 10 Hours
<u>Oral</u>		
LD50	Dog	5.5 g/kg
	Guinea pig	5.6 g/kg
	Mouse	3450 mg/kg
	Rat	6.2 g/kg

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
Formaldehyde Regulatory (CAS 50-00-0)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	0.414 mg/l, 4 Hours
		0.4 mg/l, 2 Hours
	Rat	0.82 mg/l, 0.5 Hours
		0.48 mg/l, 4 Hours
Oral		
LD50	Guinea pig	260 mg/kg
	Mouse	42 mg/kg
	Rat	100 mg/kg
Isobutyl Alcohol (CAS 78-83-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	3392 mg/kg
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
LD50	Guinea pig	19.9 mg/l
	Rabbit	26.25 mg/l
	Rat	19.2 mg/l
Oral		
LD50	Mouse	3500 mg/kg
	Rat	2.46 g/kg
Isopropanol (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12800 mg/kg
Oral		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
	Rabbit	5.03 g/kg
	Rat	4.7 g/kg
Methanol (CAS 67-56-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Rat	64000 ppm, 4 Hours
		87.5 mg/l, 6 Hours

Components	Species	Test Results
Oral LD50	Dog	8000 mg/kg
	Monkey	2 g/kg
	Mouse	7300 mg/kg
	Rabbit	14.4 g/kg
	Rat	5628 mg/kg
Methyl Isobutyl Ketone (CAS 108-10-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Oral		
LD50	Rat	2080 mg/kg
Phenol (CAS 108-95-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	850 mg/kg
	Rat	669 mg/kg
Oral		
LD50	Cat	0.1 g/kg
	Dog	0.5 g/kg
	Mouse	270 mg/kg
	Rat	317 mg/kg
Silica (CAS 7631-86-9)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Silicon dioxide (CAS 112945-52-5)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg
		14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm, 8 Hours
		400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
Oral		
LD50	Rat	2.6 g/kg

Components	Species	Test Results
Xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

ACGIH sensitization

Formaldehyde Regulatory (CAS 50-00-0) Sensitizer.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Crystalline Quartz Regulatory (CAS 14808-60-7)	1 Carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Formaldehyde Regulatory (CAS 50-00-0)	1 Carcinogenic to humans.
Methyl Isobutyl Ketone (CAS 108-10-1)	2B Possibly carcinogenic to humans.
Phenol (CAS 108-95-2)	3 Not classifiable as to carcinogenicity to humans.
Silica (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.
Silicon dioxide (CAS 112945-52-5)	3 Not classifiable as to carcinogenicity to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Formaldehyde Regulatory (CAS 50-00-0) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Quartz Regulatory (CAS 14808-60-7) Known To Be Human Carcinogen.

Formaldehyde Regulatory (CAS 50-00-0) Known To Be Human Carcinogen.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Barium Sulfate (CAS 7727-43-7)			
Aquatic			
Crustacea	EC50	Tubificid worm (Tubifex tubifex)	28.61 - 38.03 mg/l, 48 hours
Ethanol (CAS 64-17-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Formaldehyde Regulatory (CAS 50-00-0)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	4.3 - 7.8 mg/l, 48 hours
Fish	LC50	Striped bass (Morone saxatilis)	10.302 - 16.743 mg/l, 96 hours
Isobutyl Alcohol (CAS 78-83-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	950 - 1200 mg/l, 48 hours
Fish	LC50	Bleak (Alburnus alburnus)	1000 - 3000 mg/l, 96 hours
Isopropanol (CAS 67-63-0)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Methyl Isobutyl Ketone (CAS 108-10-1)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	492 - 593 mg/l, 96 hours
Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Phenol (CAS 108-95-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia obtusa)	4.7 - 6.4 mg/l, 48 hours
Fish	LC50	Asiatic knifefish (Notopterus notopterus)	8 - 8.25 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

Components		Species	Test Results
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethanol	-0.31
Ethylbenzene	3.15
Formaldehyde Regulatory	0.35
Isobutyl Alcohol	0.76
Isopropanol	0.05
Methanol	-0.77
Methyl Isobutyl Ketone	1.31
Phenol	1.46
Toluene	2.73
Xylene	3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)

Transport hazard class(es)

Class 3
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.

IMDG

UN number UN1263

UN proper shipping name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)


Transport hazard class(es)

Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant Yes

EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT**IATA; IMDG****Marine pollutant****General information**

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium Sulfate (CAS 7727-43-7)	Listed.
Ethanol (CAS 64-17-5)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Formaldehyde Regulatory (CAS 50-00-0)	Listed.
Isobutyl Alcohol (CAS 78-83-1)	Listed.
Isopropanol (CAS 67-63-0)	Listed.
Methanol (CAS 67-56-1)	Listed.
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed.
Phenol (CAS 108-95-2)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Formaldehyde Regulatory (CAS 50-00-0)	100 LBS
Phenol (CAS 108-95-2)	1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Formaldehyde Regulatory (CAS 50-00-0)	Cancer Skin sensitization Respiratory sensitization Eye irritation Skin irritation respiratory tract irritation Acute toxicity Flammability
---------------------------------------	--

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
--------------------------	---

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
Formaldehyde Regulatory	50-00-0	100	500 lbs		
Phenol	108-95-2	1000		500 lbs	10000 lbs

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Isopropanol	67-63-0	5 - < 20
Toluene	108-88-3	5 - < 10
Ethylbenzene	100-41-4	0 < 5
Formaldehyde Regulatory	50-00-0	0 < 5
Methanol	67-56-1	0 - < 5
Methyl Isobutyl Ketone	108-10-1	0 < 5
Phenol	108-95-2	0 < 5
Xylene	1330-20-7	0 - < 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)
Formaldehyde Regulatory (CAS 50-00-0)
Methanol (CAS 67-56-1)

Methyl Isobutyl Ketone (CAS 108-10-1)
Phenol (CAS 108-95-2)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Formaldehyde Regulatory (CAS 50-00-0)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Methyl Isobutyl Ketone (CAS 108-10-1)	6715
Toluene (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Methyl Isobutyl Ketone (CAS 108-10-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

Methyl Isobutyl Ketone (CAS 108-10-1)	6715
Toluene (CAS 108-88-3)	594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon Black (CAS 1333-86-4)
Crystalline Quartz Regulatory (CAS 14808-60-7)
Ethylbenzene (CAS 100-41-4)
Formaldehyde Regulatory (CAS 50-00-0)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)
Methyl Isobutyl Ketone (CAS 108-10-1)
Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)
Phenol (CAS 108-95-2)
Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Barium Sulfate (CAS 7727-43-7)
Calcium Carbonate (CAS 1317-65-3)
Carbon Black (CAS 1333-86-4)
Crystalline Quartz Regulatory (CAS 14808-60-7)
Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)
Formaldehyde Regulatory (CAS 50-00-0)
Isobutyl Alcohol (CAS 78-83-1)
Isopropanol (CAS 67-63-0)
Methanol (CAS 67-56-1)
Methyl Isobutyl Ketone (CAS 108-10-1)
Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)
Phenol (CAS 108-95-2)
Silica (CAS 7631-86-9)
Silicon dioxide (CAS 112945-52-5)
Titanium Dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Barium Sulfate (CAS 7727-43-7)
Calcium Carbonate (CAS 1317-65-3)
Carbon Black (CAS 1333-86-4)
Crystalline Quartz Regulatory (CAS 14808-60-7)
Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)

Formaldehyde Regulatory (CAS 50-00-0)
 Isobutyl Alcohol (CAS 78-83-1)
 Isopropanol (CAS 67-63-0)
 Methanol (CAS 67-56-1)
 Methyl Isobutyl Ketone (CAS 108-10-1)
 Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)
 Phenol (CAS 108-95-2)
 Silica (CAS 7631-86-9)
 Titanium Dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Barium Sulfate (CAS 7727-43-7)
 Calcium Carbonate (CAS 1317-65-3)
 Carbon Black (CAS 1333-86-4)
 Crystalline Quartz Regulatory (CAS 14808-60-7)
 Ethanol (CAS 64-17-5)
 Ethylbenzene (CAS 100-41-4)
 Formaldehyde Regulatory (CAS 50-00-0)
 Isobutyl Alcohol (CAS 78-83-1)
 Isopropanol (CAS 67-63-0)
 Methanol (CAS 67-56-1)
 Methyl Isobutyl Ketone (CAS 108-10-1)
 Petroleum Distillates, Hydrotreated Light Regulatory (CAS 64742-47-8)
 Phenol (CAS 108-95-2)
 Silica (CAS 7631-86-9)
 Silicon dioxide (CAS 112945-52-5)
 Titanium Dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)
 Formaldehyde Regulatory (CAS 50-00-0)
 Isobutyl Alcohol (CAS 78-83-1)
 Isopropanol (CAS 67-63-0)
 Methanol (CAS 67-56-1)
 Methyl Isobutyl Ketone (CAS 108-10-1)
 Phenol (CAS 108-95-2)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Crystalline Quartz Regulatory (CAS 14808-60-7)	Listed: October 1, 1988
Ethanol (CAS 64-17-5)	Listed: April 29, 2011
	Listed: July 1, 1988
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Formaldehyde Regulatory (CAS 50-00-0)	Listed: January 1, 1988
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed: November 4, 2011
Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethanol (CAS 64-17-5)	Listed: October 1, 1987
Methanol (CAS 67-56-1)	Listed: March 16, 2012
Methyl Isobutyl Ketone (CAS 108-10-1)	Listed: March 28, 2014
Toluene (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-22-2015

Version # 01

Disclaimer Medallion Refinish System cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.