SAFETY DATA SHEET



1. Identification

Product identifier Frost Blue Pearl

Other means of identification

Product code MRP-092
Recommended use Additive

Recommended restrictions No other uses are advised. **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company name Medallion Refinish System
Address 5751 N. Webster Street
Dayton, OH 45414

United States

Telephone TECH SUPPORT 937-890-6547

SALES 937-890-6547 PHONE 800-257-6547

Website www.medallion.omnispear.com

E-mail info@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F 800-257-6547

7:45am-4:30pm

EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 2

Carcinogenicity

Category 2

Category 2

Category 2

Category 2

Category 2

Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Toxic in contact with skin. Causes skin irritation. Causes serious eye

irritation. Suspected of causing cancer. Causes damage to organs through prolonged or repeated

exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective

clothing/eye protection/face protection.

Material name: Frost Blue Pearl SDS US

If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with Response

plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off immediately all

contaminated clothing and wash it before reuse.

Storage Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information 86.5% of the mixture consists of component(s) of unknown acute oral toxicity. 86.5% of the

mixture consists of component(s) of unknown acute dermal toxicity. 96.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 96.5% of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Mica Regulatory		12001-26-2	40 - < 50
Titanium Dioxide		13463-67-7	40 - < 50
2-butoxyethanol		111-76-2	10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical

advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Severe eve irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting Use water spray to cool unopened containers.

equipment/instructions

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

Material name: Frost Blue Pearl

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Co	ntaminants (29 CFR 1910.1000)
--------------------------------------	-------------------------------

Components	Туре	Value	Form
2-butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Туре	Value	Form
Mica Regulatory (CAS 12001-26-2)	TWA	20 mppcf	
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	Form
2-butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Mica Regulatory (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	Form
2-butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
,		5 ppm	

Material name: Frost Blue Pearl sps us

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Mica Regulatory (CAS	TWA	3 mg/m3	Respirable.

12001-26-2) Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA),	Creatinine in urine	*
		with hydrolysis		

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection

Wear appropriate thermal protective clothing, when necessary.

Thermal hazards



General hygiene considerations

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateSolid.FormPowder.

Color Pearlescent Blue
Odor Hydrocarbon-like.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -102.64 °F (-74.8 °C) estimated Initial boiling point and boiling 335.12 °F (168.4 °C) estimated

range

Material name: Frost Blue Pearl sps us

MRP-092 Version #: 02 Revision date: 05-02-2017 Issue date: 09-24-2015

Flash point 140.0 °F (60.0 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 3272.7 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 460.4 °F (238 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 3.20 g/cm3 estimated

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

Percent volatile 10 w/w % By Weight

29.29 v/v % By Volume

Specific gravity 3.2 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Toxic in contact with skin. Causes skin irritation.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Coughing. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Toxic in contact with skin. Harmful if swallowed.

Material name: Frost Blue Pearl SDS US

Species Test Results Components

2-butoxyethanol (CAS 111-76-2)

Acute

Dermal

LD50 Rabbit 400 mg/kg

Oral

LD50 Rat 560 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Causes serious eye irritation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

3 Not classifiable as to carcinogenicity to humans. 2-butoxyethanol (CAS 111-76-2)

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. May be harmful if absorbed

through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Components **Species Test Results**

2-butoxyethanol (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

Titanium Dioxide (CAS 13463-67-7)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours LC50 Fish Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-butoxvethanol 0.83

Material name: Frost Blue Pearl SDS US

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number UN1263

UN proper shipping name Paint related material including paint thinning, drying, removing, or reducing compound

Transport hazard class(es)

3 Class Subsidiary risk 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

149, B52, IB2, T4, TP1, TP8, TP28 Special provisions

Packaging exceptions 150 Packaging non bulk 173 Packaging bulk 242

IATA

UN number UN1263

UN proper shipping name Paint related material (including paint thinning or reducing compounds)

Transport hazard class(es)

Class 3 Subsidiary risk Packing group П **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid **UN** proper shipping name

lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant Nο F-E, S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Frost Blue Pearl SDS US Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-butoxyethanol (CAS 111-76-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 2-butoxyethanol
 111-76-2
 10 - < 20</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

Material name: Frost Blue Pearl
MRP-092 Version #: 02 Revision date: 05-02-2017 Issue date: 09-24-2015

SDS US

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-butoxyethanol (CAS 111-76-2) Titanium Dioxide (CAS 13463-67-7)

International Inventories

Australia

Country(s) or region

	• • • • • • • • • • • • • • • • • • • •	
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

Australian Inventory of Chemical Substances (AICS)

16. Other information, including date of preparation or last revision

 Issue date
 09-24-2015

 Revision date
 05-02-2017

Version # 02

Disclaimer Medallion Refinish System cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Frost Blue Pearl SDS US

On inventory (yes/no)*

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).