SAFETY DATA SHEET



1. Identification

Product identifier Primer Tint Blue

Other means of identification

Product code RS-756

Recommended use Specialty Primer

Recommended restrictions No other uses are advised. **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company nameMedallion Refinish SystemAddress5751 N. Webster StreetDavton, OH 45414

United States

Telephone TECH SUPPORT

TECH SUPPORT 937-890-6547 SALES 937-890-6547 PHONE 800-257-6547

Websitewww.medallionrefinish.comE-mailinfo@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F

7:45am-4:30pm

EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

800-257-6547

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2AGerm cell mutagenicityCategory 1BCarcinogenicityCategory 1BEnvironmental hazardsHazardous to the aquatic environment, acuteCategory 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause genetic defects. May

cause cancer. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Category 3

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

77% of the mixture consists of component(s) of unknown acute oral toxicity. 77% of the mixture consists of component(s) of unknown acute dermal toxicity. 57% of the mixture consists of component(s) of unknown acute inhalation toxicity. 74% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 74% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Glycol Ether PM Acetate		108-65-6	50 - < 70
C.I. Pigment Blue 15		147-14-8	10 - < 30
Solvent Naphtha, petroleum, light aromatic		64742-95-6	0 - < 5
Trimetyl Benzene		95-63-6	0 - < 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eve contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Ingestion

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

of ignition and flash back. During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Fire fighting

equipment/instructions Specific methods

General fire hazards

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Solvent Naphtha. PEL

Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)

95-63-6)

400 mg/m3

100 ppm

Value

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form	
C.I. Pigment Blue 15 (CAS TWA 147-14-8)	1 mg/m3	Dust and mist.		
		0.2 mg/m3	Fume.	
Trimetyl Benzene (CAS	TWA	25 ppm		

Components	Туре	Value	Form
C.I. Pigment Blue 15 (CAS 147-14-8)	TWA	1 mg/m3	Dust and mist
Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)	TWA	400 mg/m3	
,		100 ppm	
Trimetyl Benzene (CAS 95-63-6)	TWA	125 mg/m3	
,		25 ppm	

Material name: Primer Tint Blue SDS US

RS-756 Version #: 02 Revision date: 09-28-2017 Issue date: 11-03-2015

US. Workplace Environmental Exposure Level (WEEL) Guides

Components Type Value

Glycol Ether PM Acetate

(CAS 108-65-6)

TWA

50 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Glycol Ether PM Acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Blue
Odor Solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -85 °F (-65 °C) estimated
Initial boiling point and boiling 295 °F (146.11 °C) estimated

range

Flash point 113.9 °F (45.5 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 39.05 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 0.73 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible II estimated

Oxidizing properties Not oxidizing.

Percent volatile 62 w/w % By Weight 64.44 v/v % By Volume

Specific gravity 0.73 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Trimetyl Benzene (CAS 95-63-6)

Acute Dermal

LD50 Rabbit > 3160 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results	
Solvent Naphtha, petr	oleum, light aromat	ic (CAS 64742-95-6)		
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours	
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours	
			8.8 mg/l, 96 hours	
Trimetyl Benzene (CA	AS 95-63-6)			
Aquatic				

^{*} Estimates for product may be based on additional component data not shown.

LC50

Persistence and degradability

Fish

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

this material to drain into sewers water supplies. Do not containinate points, waterways of utilities

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number UN1263

UN proper shipping name Paint related material including paint thinning, drying, removing, or reducing compound

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) П Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 149, B52, IB2, T4, TP1, TP8, TP28

Packaging exceptions 150 Packaging non bulk 173 Packaging bulk 242

IATA

UN1263 **UN** number

UN proper shipping name Transport hazard class(es) Paint related material (including paint thinning or reducing compounds)

3 Class Subsidiary risk П Packing group **Environmental hazards** No. **ERG Code** 3L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid **UN proper shipping name**

lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No.

F-E, S-E **EmS**

Transport in bulk according to Annex II of MARPOL 73/78 and

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

the IBC Code





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

C.I. Pigment Blue 15 (CAS 147-14-8) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Trimetyl Benzene	95-63-6	0 - < 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)

Trimetyl Benzene (CAS 95-63-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Country(s) or region Inventory name On inventory (yes/no)* Europe European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 11-03-2015

 Revision date
 09-28-2017

Version # 02

Disclaimer Medallion Refinish System cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.