

1. Identification

Product identifier Select Shade Black Rapid Production 2K Urethane Primer Surfacers

Other means of identification

Product code RS-790B

Recommended use Primer

Recommended restrictions No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Medallion Refinish System

Address 5751 N. Webster Street
 Dayton, OH 45414
 United States

Telephone TECH SUPPORT 937-890-6547
 SALES 937-890-6547
 PHONE 800-257-6547

Website www.medallionrefinish.com

E-mail info@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F 800-257-6547
 7:45am-4:30pm
 EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2A
 Germ cell mutagenicity Category 2
 Carcinogenicity Category 1A
 Reproductive toxicity Category 2
 Specific target organ toxicity, repeated exposure Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
 Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Combustible dust

Label elements



Signal word Danger

Hazard statement May form combustible dust concentrations in air. Causes serious eye irritation. Suspected of causing genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Prevent dust accumulation to minimize explosion hazard. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Observe good industrial hygiene practices.

Response	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	62.27% of the mixture consists of component(s) of unknown acute oral toxicity. 62.27% of the mixture consists of component(s) of unknown acute dermal toxicity. 71.65% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 71.65% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Talc		14807-96-6	20 - < 40
Barium Sulfate		7727-43-7	10 - < 30
Glycol Ether PM Acetate		108-65-6	5 - < 10
Tert Butyl Acetate		540-88-5	5 - < 10
BENZENE, M-DIMETHYL-		108-38-3	3 - < 5
Tremolite (Non-asbestiform)		14567-73-8	0 - < 5
BENZENE, O-DIMETHYL		95-47-6	1 - < 3
BENZENE, P-DIMETHYL-		106-42-3	1 - < 3
ETHYLBENZENE		100-41-4	1 - < 3
Carbon Black		1333-86-4	0< 1
Crystalline Quartz		14808-60-7	0< 1
Phosphoric Acid Regulatory		7664-38-2	0< 1
Silicon Dioxide (as Amorphous Silica; See Silica), Particulate		112945-52-5	0< 1
tert-Butyl Alcohol		75-65-0	0< 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing media carefully to avoid creating airborne dust. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
-------------------------------------	--

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	May form combustible dust concentrations in air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Prevent product from entering drains. Stop the flow of material, if this is without risk. Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Explosion-proof general and local exhaust ventilation. Do not breathe dust. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Tremolite (Non-asbestiform) (CAS 14567-73-8)	STEL	1 fibers/cm3

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value	
	TWA	0.1 fibers/cm3	
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
BENZENE, M-DIMETHYL- (CAS 108-38-3)	PEL	15 mg/m3 435 mg/m3	Total dust.
BENZENE, O-DIMETHYL (CAS 95-47-6)	PEL	100 ppm 435 mg/m3	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	PEL	100 ppm 435 mg/m3	
Carbon Black (CAS 1333-86-4)	PEL	100 ppm 3.5 mg/m3	
Crystalline Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3	
Tert Butyl Acetate (CAS 540-88-5)	PEL	100 ppm 950 mg/m3	
		200 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Crystalline Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Talc (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	150 ppm	
	TWA	100 ppm	
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	150 ppm	
	TWA	100 ppm	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	150 ppm	
	TWA	100 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Tert Butyl Acetate (CAS 540-88-5)	STEL	150 ppm	Fiber.
	TWA	50 ppm	
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/cm3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	655 mg/m3	
	TWA	150 ppm	
		435 mg/m3	
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	100 ppm	
		655 mg/m3	
	TWA	150 ppm	
		435 mg/m3	
		100 ppm	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	655 mg/m3	
	TWA	150 ppm	
		435 mg/m3	
		100 ppm	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	Respirable dust.
Crystalline Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	125 ppm	Respirable.
		435 mg/m3	
		100 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	
Tert Butyl Acetate (CAS 540-88-5)	TWA	950 mg/m3	
		200 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, M-DIMETHYL- (CAS 108-38-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, O-DIMETHYL (CAS 95-47-6)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, P-DIMETHYL- (CAS 106-42-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

US - California OELs: Skin designation

Glycol Ether PM Acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.



General hygiene considerations

Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Solid.

Form

Solid.

Color

Black

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-72.67 °F (-58.15 °C) estimated

Initial boiling point and boiling range

208 °F (97.78 °C) estimated

Flash point

39.0 °F (3.9 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1.1 % estimated

Flammability limit - upper (%)

6.6 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

10.29 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

799 °F (426.11 °C) estimated

Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.98 g/cm3 estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	1.98 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Minimize dust generation and accumulation.
Incompatible materials	Nitrates. Aluminum. Phosphorus.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
BENZENE, M-DIMETHYL- (CAS 108-38-3)		
<u>Acute</u>		
Oral		
LD50	Rat	4300 mg/kg
BENZENE, O-DIMETHYL (CAS 95-47-6)		
<u>Acute</u>		
Oral		
LD50	Rat	4300 mg/kg
BENZENE, P-DIMETHYL- (CAS 106-42-3)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 - 8600 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Oral		
LD50	Rat	3500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.

Respiratory or skin sensitization**Respiratory sensitization** Not a respiratory sensitizer.**Skin sensitization** This product is not expected to cause skin sensitization.**Germ cell mutagenicity** Suspected of causing genetic defects.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, M-DIMETHYL- (CAS 108-38-3)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, O-DIMETHYL (CAS 95-47-6)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, P-DIMETHYL- (CAS 106-42-3)	3 Not classifiable as to carcinogenicity to humans.
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Crystalline Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Talc (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
	3 Not classifiable as to carcinogenicity to humans.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Tremolite (Non-asbestiform) (CAS 14567-73-8)	Cancer
--	--------

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	Known To Be Human Carcinogen.

Reproductive toxicity Suspected of damaging fertility or the unborn child.**Specific target organ toxicity - single exposure** Not classified.**Specific target organ toxicity - repeated exposure** Causes damage to organs through prolonged or repeated exposure.**Aspiration hazard** Not an aspiration hazard.**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.**12. Ecological information****Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Barium Sulfate (CAS 7727-43-7)			
Aquatic			
Crustacea	EC50	Tubificid worm (Tubifex tubifex)	28.61 - 38.03 mg/l, 48 hours
BENZENE, M-DIMETHYL- (CAS 108-38-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	2.81 - 5 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.4 mg/l, 96 hours
BENZENE, O-DIMETHYL (CAS 95-47-6)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	0.78 - 2.51 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5.59 - 11.6 mg/l, 96 hours
BENZENE, P-DIMETHYL- (CAS 106-42-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	3.55 - 6.31 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Tert Butyl Acetate (CAS 540-88-5)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	296 - 362 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BENZENE, M-DIMETHYL-	3.2
BENZENE, O-DIMETHYL	3.12
BENZENE, P-DIMETHYL-	3.15
ETHYLBENZENE	3.15
Tert Butyl Acetate	1.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150

Packaging non bulk	173
Packaging bulk	242
IATA	
UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Tremolite (Non-asbestiform) (CAS 14567-73-8)

0.1 % Annual Export Notification required.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium Sulfate (CAS 7727-43-7)	Listed.
BENZENE, M-DIMETHYL- (CAS 108-38-3)	Listed.
BENZENE, O-DIMETHYL (CAS 95-47-6)	Listed.
BENZENE, P-DIMETHYL- (CAS 106-42-3)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
Tert Butyl Acetate (CAS 540-88-5)	Listed.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Tremolite (Non-asbestiform) (CAS 14567-73-8)	Cancer Lung
--	----------------

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
--------------------------	---

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BENZENE, M-DIMETHYL-	108-38-3	3 - < 5
BENZENE, O-DIMETHYL	95-47-6	1 - < 3
BENZENE, P-DIMETHYL-	106-42-3	1 - < 3
ETHYLBENZENE	100-41-4	1 - < 3
Tremolite (Non-asbestiform)	14567-73-8	0 - < 5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE, M-DIMETHYL- (CAS 108-38-3)
BENZENE, O-DIMETHYL (CAS 95-47-6)
BENZENE, P-DIMETHYL- (CAS 106-42-3)
ETHYLBENZENE (CAS 100-41-4)
Tremolite (Non-asbestiform) (CAS 14567-73-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003
Crystalline Quartz (CAS 14808-60-7) Listed: October 1, 1988
ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004
Tremolite (Non-asbestiform) (CAS 14567-73-8) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE, METHYL- (CAS 108-88-3) Listed: January 1, 1991

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BENZENE, M-DIMETHYL- (CAS 108-38-3)
BENZENE, O-DIMETHYL (CAS 95-47-6)
BENZENE, P-DIMETHYL- (CAS 106-42-3)
Carbon Black (CAS 1333-86-4)
Crystalline Quartz (CAS 14808-60-7)
ETHYLBENZENE (CAS 100-41-4)
Talc (CAS 14807-96-6)
Tremolite (Non-asbestiform) (CAS 14567-73-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-10-2016
Revision date	12-12-2017
Version #	03
Further information	Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Disclaimer	Medallion Refinish System cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.
Revision information	Product and Company Identification: Alternate Trade Names