



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Phone 937-890-6547
Toll Free 800-257-6547
Fax 937-890-6320


MRS-122

TECHNICAL DATA

Basecoat Activator

DESCRIPTION:

MRS-122 Basecoat Activator is a uniquely formulated activator that can be used in conjunction with other paint manufacturers' basecoats to increase durability and longevity of the paint system.



FEATURES:

- ✓ Decrease dry spray
- ✓ Better intercoat adhesion
- ✓ Reduce mottling
- ✓ Increase gloss holdout
- ✓ Better chip resistance
- ✓ Improve recoat/repairability



INSTRUCTIONS:

Add 1-2 ozs. of **MRS-122 Basecoat Activator** per sprayable quart of basecoat.

MIXING:

Mix basecoat according to paint manufacturers recommendations. Add 1-2 ounces of **MRS-122 Basecoat Activator** per sprayable quart. Use ½ paint manufacturers' recommended amount in BASF basecoats



APPLICATION:

Apply product according to paint manufacturers' recommendations.






www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Phone 937-890-6547
Toll Free 800-257-6547
Fax 937-890-6320

TECHNICAL DATA

Color	Water Clear
Activator/Hardener	N/A
Reducer	
Mix Ratio	1-2 ozs. / sprayable quart
Pot Life	N/A
Number of Coats	N/A
Flash Time	N/A
Recoat w/o sanding	N/A
Dry to Sand	N/A
Air Dry 70°F (21°C) 50% RH	N/A
Force Dry	N/A
Gun Set-Up Gravity Feed (HVLP)	N/A
Air Pressure @ Gun (HVLP)	
Air Pressure @ Gun (Conventional)	
V.O.C. Limit	N/A
Sprayable V.O.C.*	
Actual	2.46 lbs/gal (295 g/l)
Regulatory	2.46 lbs/gal (295 g/l)
% Solids Sprayable by Weight	70.0%
Cov. Sq. Ft. / gal @ 1 mil*	N/A
Package	Pints & Quarts
Number per case	6
Shelf Life	12 months



RUBBER-SEAL®
Material Safety Data Sheet (MSDS) is available on our website
www.medallionrefinish.com

MedallionTM
Refinish System