5751 N. Webster Street Dayton, OH 45414-0802 Dayton 937-890-6547 Toll Free 800-257-6547 Fax 937-890-6320

www.medallionrefinish.com

# MRS-3095

# TECHNICAL DATA

### **Basecoat Stabilizer**

#### **DESCRIPTION:**

MRS-3095 Basecoat Stabilizer Hi-Temp is a direct replacement for Sherwin Williams BCS 95 Basecoat Stabilizer use in the Ultra 7000® Basecoat Intermix color system and Martin Senour BCS4 for Tec/Base.



### **INSTRUCTIONS:**

Shake well before use. Use according to paint manufacturer's mixing recommendations. Reseal after each use.

Note: MRS-122 Basecoat Activator must be used with this stabilizer. The mix ratio is 16:16:1 or 1 oz. of MRS-122 Basecoat Activator per sprayable quart.

# **APPLICATION:**

Apply product according to paint manufacturer's recommendations. Store product at 60°F to 95°F

# V.O.C.

Regulatory: 7.0 lbs/gal. Actual 7.0 lbs/gal

# **Part Numbers**

MRS-3095 Basecoat Stabilizer Hi-Temp-gallon (4 per case)

DISCLAMER: Sherwin Williams and Ultra 7000 are registered trade names of the Sherwin Williams Co. Sherwin Williams does not manufacture, endorse or guarantee Rubber-Seal Products or Medallion™ Refinish System products.

# **Health and Safety:**

### See Material Safety Data Sheet and labels for additional safety information and handling instructions.

- \* The contents of this package may have to be blended with other components before the product can be used.

  Before opening the packages, be sure you understand the warning messages on the labels and MSDS's of all components, since the mixture will have the hazards of all its parts.
- \* Improper handling and use, for example, poor spray technique, inadequate engineering controls and or lack of Personal Protective Equipment (PPE), may result in hazardous conditions or injury.
- \* Follow spray equipment manufacturer's instructions to prevent personal injury or fire.
- \* Provide adequate ventilation for health and fire hazard control.
- \* Follow company, product MSDS and respirator manufacturer's recommendations for selection and proper use of respiratory protection. Be sure employees are adequately trained on the safe use of respirators per company and regulatory requirements.
- \* Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on
- \* Always observe all applicable precautions and follow good safety and hygiene practices.
- \* Material Safety Data Sheets are available at www.medallionrefinish.com.

# FOR PROFESSIONAL USE ONLY

