

PRODUCT DESCRIPTION **MRT-98LV** is a 3.5 V.O.C. basecoat designed for overall refinishing. This **Bright White Basecoat** has excellent hiding capability and exceptional gloss holdout. It is available in quarts or gallons and V.O.C. compliant across North America.



SUITABLE SUBSTRATES

2K Urethane Primer Surfacer	2K Urethane Sealers
2K Epoxy Sealers	1K Acrylic Sealers



MIXING

1 part	:	1 or 1-1/2 parts
MRT-98LV	:	MRS-165 (FAST)
		MRS-175 (MEDIUM)
		MRS-185 (SLOW)


NOTE: Make sure product is at room temperature (72°F) before mixing.

NOTE: For optimum results, add 1 to 2 ounces of **MRS-122 Basecoat Activator** to each sprayable quart.




APPLICATION

Apply 2-3 medium wet coats or until proper hiding is achieved
 Allow 5-10 minutes flash time between coats
 Gravity Fed HVLP: 1.3mm – 1.4mm fluid tip @ 40 – 45 psi



DRY TIMES

Air Dry @ 70°F	To Topcoat	30 minutes
	To Scuff and Recoat	After 24 hours



NOTES

- Using MRS-122 Basecoat Activator will increase chip resistance and durability.
- Adding standard grade urethane reducers will increase VOCs
- For use by trained professionals only
- Read label, directions and MSDS before use
- Wear appropriate Personal Protection Equipment (PPE) while mixing and spraying

HEALTH & SAFETY

See Material Safety Data Sheet and labels for additional safety information and handling instructions.

- The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels and MSDSs of all component, since the mixture will have the hazards of all its parts.
- Improper handling and use, for example, poor spray technique, inadequate engineering controls, and or lack of Personal Protective Equipment (PPE), may result in hazardous conditions or injury.
- Follow spray equipment manufacturer's instructions to prevent personal injury or fire.
- Provide adequate ventilation for health and fire hazard control.
- Follow company, product MSDS and respirator manufacturer's recommendations for selection and proper use of respiratory protection. Be sure employees are adequately trained on the safe use of respirators per company and regulatory requirements.
- Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on MSDS.
- Always observe all applicable precautions and follow good safety and hygiene practice.
- For additional health and safety information refer to the MSDS which can be found at www.medallionrefinish.com