



www.medallionrefinish.com

5751 N. Webster Street  
Dayton, OH 45414-0802  
Phone 937-890-6547  
Toll Free 800-257-6547  
Fax 937-890-6320

## RS-582

## TECHNICAL DATA

### Paintable Rubberized Undercoat 50 State Compliant

#### DESCRIPTION:

**RS-582 Paintable Rubberized Undercoat** is a premium grade rubberized undercoat that provides rust protection and sound deadening as well as sealing out dust, fumes, heat and cold. This undercoating can be applied to a uniform light texture or a pebble like texture depending on application technique. **RS-582 Paintable Rubberized Undercoat** is paintable in four hours.

#### FEATURES:

- Convenient aerosol package-20 oz. can
- V.O.C. compliant in all 50 states
- Fast dry formula 10-15 minutes
- Minimal pin-holing-easily paintable
- Extension tube available



#### APPLICATION:

Store undercoating at room temperature (65-75°F). Shake can before use. Continue to shake can during use.

Spray thin even coats over a clean, dry surface. If more texture is desired, spray from a further distance (10-12") applying with less pressure on the spray nozzle. **RS-582 Paintable Rubberized Undercoat** will dry in about 15-20 minutes. Allow 4 hours dry time if topcoat is to be applied.



Material Safety Data Sheet (MSDS) is available on our website  
[www.medallionrefinish.com](http://www.medallionrefinish.com)

RS-582-TDS  
7/10