



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Phone 937-890-6547
Toll Free 800-257-6547
Fax 937-890-6320

RS-609

TECHNICAL DATA

Wax & Grease Remover

DESCRIPTION:

RS-609 Wax & Grease Remover is a pre-paint cleaner for all acrylic finishes. This is an excellent cleaner for removing contaminants from the surface before applying topcoats.

RS-609 Wax & Grease Remover flashes quickly leaving no residue.

V.O.C. 6.04 lbs/gal (724 g/l)

FEATURES:

- ✓ Quickly removes silicones, wax, grease and other contaminants
- ✓ Excellent final wash before applying topcoats
- ✓ Excellent wax & grease remover for cold temperatures
- ✓ Available in gallon, 5-gallon and 55-gallon

APPLICATION:

Pre-Cleaner

1. Wash surface with soap and warm water to remove dirt and other waterborne contaminants. Dry the surface before using **RS-609 Wax & Grease Remover**.
2. Apply **RS-609 Wax & Grease Remover** to a clean, dry cloth. **RS-805 Applicator** is an excellent pressurized applicator for applying this pre-cleaner
3. Wipe the area with the saturated cloth. The surface must remain wet to penetrate and dissolve any waxes and silicones.
4. Wipe the area dry with a clean, dry, lint-free cloth before the solvent evaporate.

Note: The above steps are recommended before grinding or sanding any repair area. If these steps are not followed there is a possibility of forcing contaminants into the metal or surface which could result in poor adhesion of filler and /or primer as well as topcoating issues.

Final Wash

1. Blow off area with compressed air.
2. Apply **RS-609 Wax & Grease Remover** to a clean, dry cloth
3. Wipe the area with the saturated cloth.
4. Wipe the area dry with a clean, dry, lint-free cloth before the surface dries.

Material Safety Data Sheet (MSDS) is available on our website

www.medallionrefinish.com