



www.medallionrefinish.com

5751 N. Webster Street
Dayton, OH 45414-0802
Phone 937-890-6547
Toll Free 800-257-6547
Fax 937-890-6320

RS-618

TECHNICAL DATA

Dust Trap

DESCRIPTION:

RS-618 Dust Trap is a statically charged water based clear liquid designed to attract and hold dust on spray booth floors and other dusty work areas. It attracts dust and dirt holding the particulate on ground level. **RS-618 Dust Trap** can be applied several times before removing with water.

FEATURES:

- ✓ Easy to apply with pressure sprayer
- ✓ Excellent for new spray booths
- ✓ Dries to a non-tacky surface
- ✓ Waterbase formula; rinses off with water
- ✓ No mixing, ready to spray

PREPARATION:

Sweep floor to remove existing dust and loose debris.

APPLICATION:

Apply with a pressure sprayer or hand pump sprayer.
RS-805 Pump N Clean works great.

COATS: Apply 1 light coat as needed

DRY TIME: 30-40 minutes @ 70°F (dries to light tacky coat)

DRY TO USE: 60 minutes

RECOAT: Daily if needed

COVERAGE: 584 sq. ft. / gallon depending on surface condition

CLEAN UP: Clean equipment with soap and warm water

AVAILABILITY: RS-618 gallon, RS-618-5 (5-gallon pail)



RS-805

Material Safety Data Sheet (MSDS) is available on our website
www.medallionrefinish.com