# SAFETY DATA SHEET



# 1. Identification

Product identifier HydroCut Polish

Other means of identification

Product code MRS-9660

Recommended use Automotive, Rubbing Compound

**Recommended restrictions**No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Medallion Refinish System
Address 5751 N. Webster Street
Davton. OH 45414

United States

Telephone TECH SUPPORT 937-890-6547

SALES 937-890-6547 PHONE 800-257-6547

Website www.medallion.omnispear.com

E-mail info@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F 800-257-6547

7:45am-4:30pm

EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsGerm cell mutagenicityCategory 1BCarcinogenicityCategory 1B

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Danger

Hazard statement Flammable liquid and vapor. May cause genetic defects. May cause cancer. Harmful to aquatic

life with long lasting effects.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment. Wear protective

Category 3

gloves/protective clothing/eye protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: HydroCut Polish

None known.

Supplemental information

48.24% of the mixture consists of component(s) of unknown acute oral toxicity. 48.24% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 29.02% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 29.02% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

| Mixtures                                  |                          |            |           |
|---|--------------------------|------------|-----------|
| Chemical name                             | Common name and synonyms | CAS number | %         |
| Aluminum Oxide                            |                          | 1344-28-1  | 10 - < 20 |
| Naphtha (Petoleum) Hydrotreaded Heavy     |                          | 64742-48-9 | 5 - < 10  |
| Petroleum Distillates, Hydrotreated Light |                          | 64742-47-8 | 5 - < 10  |
| White Mineral Oil                         |                          | 8042-47-5  | 5 - < 10  |
| Decamethylcyclopentasiloxane              |                          | 541-02-6   | 3 - < 5   |

## 4. First-aid measures

Sodium Hydroxide

Alcohols, C8-22, Ethoxylated

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

before reuse.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

69013-19-0

1310-73-2

< 1

< 0.1

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific methods

General fire hazards

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting
In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

Material name: HydroCut Polish

SDS US

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

## **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components   | Туре  | Value     | Form                 |
|--|-------|-----------|----------------------|
| Aluminum Oxide (CAS<br>1344-28-1)                                | PEL   | 5 mg/m3   | Respirable fraction. |
| ·  |       | 15 mg/m3  | Total dust.          |
| Naphtha (Petoleum)<br>Hydrotreaded Heavy (CAS<br>64742-48-9)     | PEL   | 400 mg/m3 |                      |
| ,  |       | 100 ppm   |                      |
| Petroleum Distillates,<br>Hydrotreated Light (CAS<br>64742-47-8) | PEL   | 400 mg/m3 |                      |
| ,  |       | 100 ppm   |                      |
| White Mineral Oil (CAS<br>8042-47-5)                             | PEL   | 5 mg/m3   | Mist.                |
| US. OSHA Table Z-3 (29 CFR 1910.                                 | 1000) |           |                      |
| Components   | Туре  | Value     | Form                 |
| Aluminum Oxide (CAS 1344-28-1)                                   | TWA   | 5 mg/m3   | Respirable fraction. |
|  |       | 15 mg/m3  | Total dust.          |
|  |       | 50 mppcf  | Total dust.          |

Material name: HydroCut Polish

SDS US

| Components   | Туре                       | Value     | Form                 |
|--|----------------------------|-----------|----------------------|
|  |                            | 15 mppcf  | Respirable fraction. |
| <b>US. ACGIH Threshold Limit Value</b>                       | s                          |           |                      |
| Components   | Туре                       | Value     | Form                 |
| Aluminum Oxide (CAS 1344-28-1)                               | TWA                        | 1 mg/m3   | Respirable fraction. |
| White Mineral Oil (CAS 8042-47-5)                            | TWA                        | 5 mg/m3   | Inhalable fraction.  |
| US. NIOSH: Pocket Guide to Chen                              | nical Hazards              |           |                      |
| Components   | Туре                       | Value     | Form                 |
| Naphtha (Petoleum)<br>Hydrotreaded Heavy (CAS<br>64742-48-9) | TWA                        | 400 mg/m3 |                      |
| ,  |                            | 100 ppm   |                      |
| White Mineral Oil (CAS 8042-47-5)                            | STEL                       | 10 mg/m3  | Mist.                |
| ,  | TWA                        | 5 mg/m3   | Mist.                |
| US. Workplace Environmental Exp                              | oosure Level (WEEL) Guides |           |                      |
| Components   | Туре                       | Value     |                      |
| Decamethylcyclopentasilox ane (CAS 541-02-6)                 | TWA                        | 10 ppm    |                      |

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards









## General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

# **Appearance**

Physical state Liquid. **Form** Liquid. Color Not available. Not available. Odor **Odor threshold** Not available. Not available.

32 °F (0 °C) estimated Melting point/freezing point Initial boiling point and boiling 149 °F (65 °C) estimated

range

Material name: HydroCut Polish SDS US

Flash point 141.8 °F (61.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.7 % estimated

Flammability limit - upper

(%)

5 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 10.27 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 1.73 g/cm3 estimated

**Explosive properties** Not explosive.

Flammability class Combustible IIIA estimated

Oxidizing properties Not oxidizing.

Percent volatile 1.45 % estimated

Specific gravity 1.73 estimated

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**Incompatible materials** Acids. Strong oxidizing agents. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

Acute toxicity Not known.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Material name: HydroCut Polish SDS US

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

White Mineral Oil (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

| otoxicity              | Harmful to         | o aquatic life with long lasting effects.           |                          |
|------------------------|--------------------|---|--------------------------|
| Components             |                    | Species   | Test Results             |
| Naphtha (Petoleum) F   | lydrotreaded Heavy | (CAS 64742-48-9)                                    |                          |
| Aquatic                |                    |   |                          |
| Crustacea              | EC50               | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours |
| Fish                   | LC50               | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours       |
|                        |                    |   | 8.8 mg/l, 96 hours       |
| Petroleum Distillates, | Hydrotreated Light | (CAS 64742-47-8)                                    |                          |
| Aquatic                |                    |   |                          |
| Crustacea              | EC50               | Water flea (Daphnia pulex)                          | 2.7 - 5.1 mg/l, 48 hours |
| Fish                   | LC50               | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours       |

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### Persistence and degradability

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Decamethylcyclopentasiloxane 5.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Material name: HydroCut Polish

## Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

#### DOT

**UN** number UN1993

UN proper shipping name Flammable liquids, n.o.s. (Naphtha (Petoleum) Hydrotreaded Heavy)

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T4, TP1, TP29 Special provisions

150 Packaging exceptions 203 Packaging non bulk Packaging bulk 242

**IATA** 

UN1993 **UN** number

UN proper shipping name

Flammable liquid, n.o.s. (Naphtha (Petoleum) Hydrotreaded Heavy)

Transport hazard class(es)

3 Class Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

Not established.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN1993 **UN** number

UN proper shipping name Transport hazard class(es) FLAMMABLE LIQUID, N.O.S. (Naphtha (Petoleum) Hydrotreaded Heavy)

Class 3 Subsidiary risk Packing group Ш

**Environmental hazards** 

Marine pollutant No. F-E, S-E **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



Material name: HydroCut Polish SDS US MRS-9660 Version #: 02 Revision date: 07-18-2017 Issue date: 07-17-2017



## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

| Chemical name  | CAS number | % by wt.  |
|----------------|------------|-----------|
| Aluminum Oxide | 1344-28-1  | 10 - < 20 |

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations California Safe Drinking

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Decamethylcyclopentasiloxane (CAS 541-02-6)

Naphtha (Petoleum) Hydrotreaded Heavy (CAS 64742-48-9)

## **International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada               | Domestic Substances List (DSL)   | No                     |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |

Material name: HydroCut Polish SDS US

Country(s) or region Inventory name On inventory (yes/no)\*

Japan Inventory of Existing and New Chemical Substances (ENCS) No

Korea Existing Chemicals List (ECL)

New ZealandNew Zealand InventoryNoPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesNo

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 07-17-2017

 Revision date
 07-18-2017

Version # 02

**Disclaimer** Medallion Refinish System cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Material name: HydroCut Polish