# SAFETY DATA SHEET



## 1. Identification

Product identifier Baracuda Aerosol Adhesion Sealer

Other means of identification

Product code RS-598
Recommended use Aerosol
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

**Company name**Address
5751 N. Webster Street
Dayton, OH 45414

United States

Telephone TECH SUPPORT

SALES 937-890-6547 PHONE 800-257-6547

Website www.medallionrefinish.com
E-mail info@rubber-seal.net

Emergency phone number MAIN OFFICE: M-F

7:45am-4:30pm

EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

937-890-6547

800-257-6547

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Category 2

Category 2

Avoid release to the environment. Wear eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: Baracuda Aerosol Adhesion Sealer

None known.

Supplemental information

83.76% of the mixture consists of component(s) of unknown acute oral toxicity. 83.76% of the mixture consists of component(s) of unknown acute dermal toxicity. 48.76% of the mixture consists of component(s) of unknown acute inhalation toxicity. 60.43% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 60.43% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	14 - < 16
Parachlorobenzotrifluoride (pcbtf		98-56-6	39
Dimethyl Ether Regulatory		115-10-6	35

## 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Most important symptoms/effects, acute and

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment

Firefighters must use standard protective equipment including flame retardant coat, helmet with

and precautions for firefighters

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with

Fire fighting equipment/instructions

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

2/9

SDS US RS-598 Version #: 02 Revision date: 05-14-2020 Issue date: 05-11-2020

# Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

## **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

## Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapors. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

## US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
Dimethyl Ether Regulatory (CAS 115-10-6)	TWA	1880 mg/m3	
		1000 ppm	

## **Biological limit values**

ACGIH Biological Exposure Indices							
Components	Value	Determinant	Specimen	Sampling Time			
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*			
* - For sampling details, please see the source document.							

Material name: Baracuda Aerosol Adhesion Sealer

# Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







## General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

## **Appearance**

Physical state Liquid, Gas. Aerosol. **Form** Not available. Color Odor Not available. **Odor threshold** Not available. Not available.

-222.7 °F (-141.5 °C) estimated Melting point/freezing point Initial boiling point and boiling -12.68 °F (-24.82 °C) estimated

range

Flash point -42.0 °F (-41.1 °C) estimated

Not available. **Evaporation rate** 

Flammability (solid, gas) Not applicable. Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2.6 % estimated

Flammability limit - upper

(%)

27 % estimated

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

2374.16 hPa estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

662 °F (350 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. Not available. Viscosity

Other information

**Density** 1.46 g/cm3 estimated

**Explosive properties** Not explosive.

Material name: Baracuda Aerosol Adhesion Sealer

RS-598 Version #: 02 Revision date: 05-14-2020 Issue date: 05-11-2020

Heat of combustion (NFPA 13

30B)

13.62 kJ/g estimated

Oxidizing properties Not oxidizing.

Percent volatile 15.67 % estimated

Specific gravity 1.46 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

-----

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** Knowledge about health hazard is incomplete.

**Eye contact** Causes serious eye irritation.

**Ingestion** Knowledge about health hazard is incomplete.

Symptoms related to the

physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

# Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Acetone (CAS 67-64-1)

Acute

**Dermal** 

LD50 Rabbit 20000 mg/kg

Inhalation

LC50 Rat 50.1 mg/l, 8 Hours

Oral

LD50 Rat 5800 mg/kg

Dimethyl Ether Regulatory (CAS 115-10-6)

**Acute** 

Inhalation

LC50 Rat 164000 ppm, 4 Hours

**Skin corrosion/irritation**Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization

Skin sensitization

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Material name: Baracuda Aerosol Adhesion Sealer

## US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

**Aspiration hazard**Due to partial or complete lack of data the classification is not possible.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components Species Test Results

Acetone (CAS 67-64-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 10294 - 17704 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout 4740 - 6330 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24 Dimethyl Ether Regulatory 0.1

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

### 14. Transport information

DOT

UN number UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable, (each not exceeding 1 L capacity), MARINE POLLUTANT

Olege 2

Class 2.1

Subsidiary risk 6.1(PGIII) Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

**Packaging exceptions** 306 Packaging non bulk None Packaging bulk None

**IATA** 

UN1950 **UN** number

Aerosols, flammable **UN** proper shipping name Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Allowed with restrictions. Cargo aircraft only

**IMDG** 

UN1950 **UN** number

**UN** proper shipping name Transport hazard class(es) Aerosols, flammable, MARINE POLLUTANT

2.1 Class Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant Yes F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT





7/9

RS-598 Version #: 02 Revision date: 05-14-2020 Issue date: 05-11-2020

### Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Parachlorobenzotrifluoride (pcbtf) (CAS 98-56-6) 1.0 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) Listed.

Dimethyl Ether Regulatory (CAS 115-10-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

**categories** Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Dimethyl Ether Regulatory (CAS 115-10-6) **Safe Drinking Water Act**Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

**US** state regulations

**California Proposition 65** 

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

RS-598 Version #: 02 Revision date: 05-14-2020 Issue date: 05-11-2020

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

#### **International Inventories**

**Philippines** 

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

No

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

No

# 16. Other information, including date of preparation or last revision

 Issue date
 05-11-2020

 Revision date
 05-14-2020

Version # 02

**Disclaimer** Medallion Refinish System cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

**Revision information** Transport Information: Proper Shipping Name/Packing Group

Material name: Baracuda Aerosol Adhesion Sealer

RS-598 Version #: 02 Revision date: 05-14-2020 Issue date: 05-11-2020

No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).