

ELITE

CAR CARE TECHNOLOGY



*For a Brilliant Reflection
on You and Your Work*

HYDRO
BUFFING SYSTEM 

POWERED BY
RUBBER-SEAL™
Medallion™
Refresh System

ELITE

HydroCut Compound



- Removes 1200 grit and finer sand scratches
- For best results, use with RS-644 Low Lint Wool Compound Pad
- Produces minimal swirl marks and haze
- Easy clean up

Part No.

MRS-9658-Q

MRS-9658-1

Size

Quart

Gallon

HydroCut Polish



- Removes swirl marks and other surface imperfections
- For best results, use with MRS-685 Foam Polishing Pad
- Easy clean up

Part No.

MRS-9660-Q

MRS-9660-1

Size

Quart

Gallon

HydroGlaze Finishing Polish



- Removes ultrafine sand scratches and minor surface imperfections
- For best results, use with MRS-686 or MRS-687 Soft Finishing Pads
- Can be applied by hand and buffed off with a clean microfiber cloth

Part No.

MRS-9662-Q

Size

Quart

HYDRO

BUFFING SYSTEM



Low Linting Blue Wool Pad



- Four ply, twisted 100% prewashed wool
- Cuts quickly with minimal linting
- Hook & loop attachment
- Ideal for scratch removal & removing light oxidation

Part No.
RS-644

Unit Qty.
1 pad

Green Foam Polishing Pad




- Medium Green Foam (~60ppi)
- Waffle face improves air flow
- Ideal for light compounding & swirl removal

Part No.
MRS-685(Recessed back)

Unit Qty.
1 pad

Light Blue Foam Soft Finishing Pad



- Extra Soft Foam (~100ppi)
- Waffle face improves air flow
- Ideal for fine finish polishing

Part No.
MRS-686 (Flat back)
MRS-687 (Recessed back)

Unit Qty.
2 pads
1 pad

ELITE

HYDRO BUFFING SYSTEM



STEP

1

- To remove sand scratches after color sanding, use MRS-9658 with a RS-644 Low Linting Wool Pad

- Apply a thick bead of MRS-9658 around the center of the pad or on the buffing surface

- Work the material over the sanded surface until sand scratches are removed



1500 - 1800 rpm

- Wipe excess material from surface with a clean microfiber cloth



STEP

2

- To remove swirl marks and fine sand scratches after compounding, use MRS-9660 with a MRS-685 Foam Polishing Pad

- Apply a thick bead of MRS-9660 around the center of the pad or on the buffing surface

- Work the material over the surface until the surface imperfections are removed



1000 - 1200 rpm

- Wipe excess material from surface with a clean microfiber cloth



STEP

3

- For the ultimate finish, use MRS-9662 with MRS-686/687 Soft Foam Finishing Pad to remove ultra fine imperfections and enhance gloss

- Apply a quarter-sized amount of MRS-9662 around the center of the pad or on the buffing surface

- Work the material over the surface until the surface imperfections are removed



800 - 1000 rpm

- Wipe excess material from surface with a clean microfiber cloth

